reSAWN TIMBER co.[™] The Value of a Natural Product is Without Equal.[™]

EURO WHITE OAK TECH SPECS

EUROPEAN WHITE OAK - RIFT & QUARTER SAWN



BAYADER Finished with UV Oil Select Grade: ENG 3/4" (6mm) X 5" wide



BRAVURA Finished with Matte Polyurethane **Select Grade:** ENG 3/4" (6mm) X 5" wide



COPPELIA Finished with Matte Polyurethane **Select Grade:** ENG 3/4" (6mm) X 5" wide



GISELLE 2.0 Finished with Matte Polyurethane **Select Grade:** ENG 3/4" (6mm) X 5" wide



RHAPSODY Finished with Matte Polyurethane Select Grade: ENG 3/4" (6mm) X 5" wide



VIRTUOSO Finished with Matte Polyurethane Select Grade: ENG 3/4" (6mm) X 5" wide



BRINATO Finished with Matte Polyurethane **Select Grade:** ENG 3/4" (6mm) X 5" wide



SAMSARA Finished with Matte Polyurethane Select Grade: ENG 3/4" (6mm) X 5" wide



PARAMITO Finished with Matte Polyurethane Select Grade: ENG 3/4" (6mm) X 5" wide



CAMPAGNA Finished with Matte Polyurethane **Select Grade:** ENG 3/4" (6mm) X 5" wide

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

reSAWN TIMBER co.

resawntimberco.com

P 215 709 2001

EUROPEAN WHITE OAK - RIFT & QUARTER SAWN

ADDITIONAL SPECIFICATIONS:

SPECIES:	European White Oak
GRADE:	Select
CUT:	Rift & Quarter Sawn
APPLICATIONS:	Interior Flooring, Wall & Ceiling Cladding
LENGTHS:	2'-10' Random Lengths
MILLING:	T&G, Endmatched
EDGES:	Microbeveled Edges and Ends
Janka Hardness (ASTM D 1037):	1,360 *
Flame Spread Class Rating (ASTM E84):	Class III (C) **

* Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

**Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2024. Testing is on unfinished, solid wood. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

reSAWN TIMBER co.

resawntimberco.com

P 215 709 2001

reSAWN TIMBER co.[™] The Value of a Natural Product is Without Equal. [™]

EURO WHITE OAK TECH SPECS

EUROPEAN WHITE OAK - CHARACTER & SELECT



ACE

Finished with Matte Polyurethane

Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



AMITY

Finished with Matte Polyurethane Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



BASTILLE Finished with Matte Polyurethane Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade:

Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



CHEERIO Finished with Matte Polyurethane Character Grade: ENG 5/8" (4mm) x 7" wide ENG 3/4" (6mm) x 7" wide ENG 3/4" (6mm) x 8-5/8" wide Select Grade: ENG 5/8" (4mm) x 7" wide

ENG 5/8" (4mm) x 7" wide ENG 3/4" (6mm) x 7" wide ENG 3/4" (6mm) x 8-5/8" wide



FAFF

Finished with Matte Polyurethane Character Grade: ENG 3/4" (5mm) X 7" wide Select Grade: ENG 3/4" (5mm) X 7" wide



BARTEK

Finished with UV Oil **Character Grade:**

Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide

ENG 3/4" (6mm) X 8-5/8" wide



BOLLOCKS Finished with UV Oil Character Grade: ENG 3/4" (6mm) X 7" wide



POSH 2.0 Finished with Matte Polyurethane Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

reSAWN TIMBER co.

resawntimberco.com

P 215 709 2001

reSAWN TIMBER co.[™] The Value of a Natural Product is Without Equal. [™]

EURO WHITE OAK TECH SPECS

EUROPEAN WHITE OAK - CHARACTER & SELECT



FORTNIGHT Finished with UV Oil Character Grade: ENG 3/4" (6mm) X 7" wide



GOVERNOR Finished with UV Oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide

ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



KIP Finished with UV Oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide

ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



MARGOT Finished with UV Oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



MATE

Finished with UV Oil **Character Grade:**

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



MATTERHORN Finished with Hardwax Oil Character Grade: ENG 3/4" (5mm) X 7" wide Select Grade: ENG 3/4" (5mm) X 7" wide



PROPER Finished with UV Oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



TOFF Finished with UV Oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

reSAWN TIMBER co.

resawntimberco.com

P 215 709 2001

reSAWN TIMBER co.™ The Value of a Natural Product is Without Equal.™

EURO WHITE OAK TECH SPECS

EUROPEAN WHITE OAK - CHARACTER & SELECT



ARBORIA

Finished with Matte Polyurethane

Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



BOSQUE Finished with Matte Polyurethane Character Grade: ENG 3/4" (5mm) X 7" wide Select Grade: ENG 3/4" (5mm) X 7" wide



FIORELLA Finished with Hardwax Oil Character Grade: ENG 3/4" (5mm) X 7" wide Select Grade: ENG 3/4" (5mm) X 7" wide



MANGATA Finished with Matte Polyurethane Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



PRASADA Finished with Hardwax Oil Character Grade: ENG 3/4" (5mm) X 7" wide Select Grade: ENG 3/4" (5mm) X 7" wide



SELVATICO Finished with Matte Polyurethane **Character Grade:** ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide

ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



SONDER Finished with Hardwax Oil Character Grade: ENG 3/4" (5mm) X 7" wide Select Grade: ENG 3/4" (5mm) X 7" wide



VENTOSO Finished with UV Oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

reSAWN TIMBER co.

resawntimberco.com

P 215 709 2001

reSAWN TIMBER co.™

The Value of a Natural Product is Without Equal.™

EURO WHITE OAK TECH SPECS

EUROPEAN WHITE OAK - CHARACTER & SELECT



VERDANT Finished with Matte Polyurethane Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

ADDITIONAL SPECIFICATIONS:

SPECIES:	European White Oak
GRADE:	Character and Select
CUT:	Original (If Character), Plain Sawn (If Select)
APPLICATIONS:	Interior Flooring, Wall & Ceiling Cladding
LENGTHS:	2'-10' Random Lengths
MILLING:	T&G, Endmatched
EDGES:	Microbeveled Edges and Ends
Janka Hardness (ASTM D 1037):	1,360 *
Flame Spread Class Rating (ASTM E84):	Class III (C) **

* Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

**Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2024. Testing is on unfinished, solid wood. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

reSAWN TIMBER co.

resawntimberco.com

P 215 709 2001

reSAWN TIMBER co.™

The Value of a Natural Product is Without Equal.™

EUROPEAN WHITE OAK - CHARRED



KAIZEN Finished with Hardwax Oil Shou Sugi Ban Charred Select Grade: ENG +/- 3/4" (6mm) X +/- 7" wide

ADDITIONAL SPECIFICATIONS:

SPECIES:	European White Oak
GRADE:	Select
CUT:	Plain Sawn
APPLICATIONS:	Interior Wall & Ceiling Cladding
LENGTHS:	2'-10' Random Lengths
MILLING:	T&G, Endmatched
EDGES:	Microbeveled Edges and Ends
Janka Hardness (ASTM D 1037):	1,360 *
Flame Spread Class Rating (ASTM E84):	Class III (C) **

* Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

**Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2024. Testing is on unfinished, solid wood. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

reSAWN TIMBER co.

resawntimberco.com

P 215 709 2001

GRADING GUIDELINES:

Character Grade

This grade includes filled knots up to approximately 2" diameter, star knots up to approximately 2-1/2" diameter, limited checking, and the presence of sap wood. Greater tonal variation will be present. Slight milling imperfections and torn grain may be present in limited areas as well as limited brown streaking and worm holes. Fill will be brown or black in tone.

Select Grade

This grade includes occasional small, sound filled knots up to approximately 5/8" diameter. Sap wood is very limited. Tone within the grade tends to be more consistent as compared to Character Grade. Limited pin worm holes and slight checking may be present. Fill, if present, will be brown or black in tone.

AVAILABLE CUTS:

Rift & Quarter Sawn

This cut includes a combination of quarter sawn and rift sawn material.

Quarter sawn patterning is characterized by growth rings between 45 and 90 degrees to the face of the board, often resulting in grain lines that are mostly parallel to the length of the board with medullary ray flecks present and more than 1/16" wide.

Rift sawn patterning is characterized by growth rings between 30 and 60 degrees to the face of the board, often resulting in grain lines that are consistently parallel to the length of the board with medullary ray flecks less than 1/16" wide.

Plain Sawn

This cut includes patterning that is characterized by growth rings at 30 degrees or less to the face of the board, often resulting in a cathedral grain pattern. Some vertical and tighter grain characteristics may be present from board to board.

Original Cut

This is a method of cutting a log straight through its diameter without turning. This approach incorporates plain sawn, quarter sawn and rift sawn grain patterns in the face of the resulting boards and includes a range of character marks in the final product. Common character marks include knots, checks, streaks and worm holes.

INSTALLATION GUIDE:

- Acclimatization is vital to minimize swelling & shrinking of material
- Visit resawntimberco.com's A+D Support page to download Installation Guidelines


Application	Engineered
Above-grade	YES
On-grade	YES
Below-grade	YES
Over Radiant Heat	YES

ACCEPTABLE SUB-FLOORS AND INSTALLATION METHODS - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor: Glue-down (Engineered Recommended), Nail-down, Staple-down Concrete Sub-floor: Glue-down (Engineered Recommended)

PACKAGING AND FREIGHT: All shipments are carefully packaged on 10'-12' long pallets

EURO WHITE OAK TECH SPECS



HERRINGBONE - STANDARD DIMENSIONS & EDGE DETAIL:

	Engineered	Engineered
Thickness:	5/8" (4mm wear layer)	3/4" (6mm)
Width:	4"	4"
Lengths:	24"	24"
Edges:	Microbevel (finished)	Microbevel (finished)
	Square Edge (unfinished)	Square Edge (unfinished)
Milling:	T&G, Double End Grooved	T&G, Double End Grooved

Herringbone material in 4" width x 24" length dimensions in Select Grade, Plainsawn is available in the following products: ACE, AMITY, ARBORIA, BARTEK, BASTILLE, KIP, MANGATA, MATE, PARAMITO, POSH 2.0, PROPER, SELVATICO, VENTIOSO, and VERDANT.

Custom Herringbone options as well as Chevron options available upon request/consulation - contact reSAWN for more details.

SUSTAINABLE ATTRIBUTES:



CERTIFICATION:

POSSIBLE LEED CREDITS: MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish)

- MR 7 Certified wood (as FSC[©]-Certified)
- EQ 4.1 Low-emitting materials: Adhesives & Sealants (Engineered)
- EQ 4.2 Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish)