EUROPEAN WHITE OAK - RIFT & QUARTER SAWN



BAYADER

Finished with hardwax oil Select Grade:

ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide



BRAVURA

Finished with matte polyurethane Select Grade:

ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide



COPPELIA

Finished with matte polyurethane Select Grade:

ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide



GISELLE

Finished with matte polyurethane Select Grade:

ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide



RHAPSODY

Finished with matte polyurethane

Select Grade:

ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide



VIRTUOSO

Finished with matte polyurethane

Select Grade:

ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide

ADDITIONAL SPECIFICATIONS:

SPECIES: European White Oak CUT: Rift & Quarter Sawn

GRADE: Select

APPLICATIONS: Flooring, wall cladding, and ceiling cladding

LENGTHS: 2'-10' Random Lengths

MILLING: T&G, Endmatched

EDGES: Microbeveled Edges and Ends

1,360 * Janka Hardness (ASTM D 1037):

Flame Spread Class Rating (ASTM E84): Class III (C) **

^{*}Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

EUROPEAN WHITE OAK - CHARACTER & SELECT



ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide

ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide

ENG 3/4" (6mm) X 8-5/8" wide



Finished with matte polyurethane **Character Grade:**

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

AMITY

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



BASTILLE

Finished with matte polyurethane

Character Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



CHEERIO

Finished with matte polyurethane

Character Grade:

ENG 5/8" (4mm) x 7" wide ENG 3/4" (6mm) x 7" wide ENG 3/4" (6mm) x 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) x 7" wide ENG 3/4" (6mm) x 7" wide



DOSH

Finished with matte polyurethane

Character Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



FAFF

Finished with matte polyurethane

Character Grade:

ENG 3/4" (5mm) X 7" wide

Select Grade:

ENG 3/4" (5mm) X 7" wide



BARTEK

Finished with hardwax oil

Character Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide



BOLLOCKS

Finished with hardwax oil

Character Grade:

ENG 3/4" (6mm) X 7" wide

EUROPEAN WHITE OAK - CHARACTER & SELECT



FORTNIGHT Finished with hardwax oil Character Grade: ENG 3/4" (6mm) X 7" wide



GOVERNOR Finished with hardwax oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide

ENG 3/4" (6mm) X 7" wide



KIP Finished with hardwax oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide

ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide





ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide

Finished with hardwax oil

Character Grade:



MATTERHORN Finished with hardwax oil **Character Grade:** ENG 3/4" (5mm) X 7" wide Select Grade: ENG 3/4" (5mm) X 7" wide



Finished with hardwax oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 5" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide





ENG 5/8" (4mm) X 7" wide

ENG 3/4" (6mm) X 7" wide

TOFF Finished with hardwax oil Character Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide ENG 3/4" (6mm) X 8-5/8" wide Select Grade: ENG 5/8" (4mm) X 7" wide ENG 3/4" (6mm) X 7" wide



EUROPEAN WHITE OAK - CHARACTER & SELECT



POSH 2.0 Finished with matte polyurethane

Character Grade:

ENG 5/8" (4mm) X 7" wide

ENG 3/4" (6mm) X 5" wide

ENG 3/4" (6mm) X 7" wide

ENG 3/4" (6mm) X 8-5/8" wide

Select Grade:

ENG 5/8" (4mm) X 7" wide

ENG 3/4" (6mm) X 5" wide

ENG 3/4" (6mm) X 7" wide

ENG 3/4" (6mm) X 8-5/8" wide

ADDITIONAL SPECIFICATIONS:

SPECIES: European White Oak

APPLICATIONS: Flooring, wall cladding, and ceiling cladding

LENGTHS: 2'-10' Random Lengths

MILLING: T&G, Endmatched

FDGFS: Microbeveled Edges and Ends

Janka Hardness (ASTM D 1037): 1,360 *

Flame Spread Class Rating (ASTM E84): Class III (C) **

^{*}Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

^{**}Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2017. Testing is on unfinished, solid wood see attached for additional details. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

EUROPEAN WHITE OAK - CHARRED




KAIZEN Finished with hardwax oil shou sugi ban charred Select Grade:

ENG +/- 3/4" (6mm) X +/- 7" wide



Finished with hardwax oil shou sugi ban charred Select Grade:

ENG +/- 3/4" (6mm) X +/- 7" wide



PAI SHO Finished with hardwax oil shou sugi ban charred Select Grade: ENG +/- 3/4" (6mm) X +/- 7" wide

ADDITIONAL SPECIFICATIONS:

SPECIES: European White Oak

APPLICATIONS: Wall cladding and ceiling cladding

LENGTHS: 2'-10' Random Lengths

MILLING: T&G, Endmatched

EDGES: Microbeveled Edges and Ends

Janka Hardness (ASTM D 1037): 1.360 *

Flame Spread Class Rating (ASTM E84): Class III (C) **

^{*}Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

^{**}Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2017. Testing is on unfinished, solid wood - see attached for additional details. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

GRADING GUIDELINES:

Character Grade

Our character grade highlights the natural features in European Oak. We allow for a culled presence of knots, cracks and sapwood. The allowance of up to 2" diameter knots, and open knots of up to 3/4" create a flooring grade that is both natural and sophisticated. Open voids are filled with a dark brown epoxy prior to finishing.

Select Grade

Our select grade highlights the tonal uniformity and clarity of an elevated grade of European Oak. We allow for occasional pin knots and small filled knots up to 5/8" in diameter. Efforts are made to cull sap, but some edge or end sap may be present.

INSTALLATION GUIDE:

- Acclimatization is vital to minimize swelling & shrinking of material
- Visit resawntimberco.com's A+D Support page to download Installation Guidelines


Application	Engineered
Above-grade	YES
On-grade	YES
Below-grade	YES
Over Radiant Heat	YES

ACCEPTABLE SUB-FLOORS AND INSTALLATION METHODS - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor: Glue-down, Nail-down, Staple-down

Concrete Sub-floor: Glue-down

PACKAGING AND FREIGHT: All shipments are carefully packaged on 12' long pallets



HERRINGBONE - STANDARD DIMENSIONS & EDGE DETAIL:

	Engineered	Engineered
Thickness:	5/8" (4mm wear layer)	3/4" (6mm)
Width:	4"	4"
Lengths:	24"	24"
Edges:	Microbevel (finished)	Microbevel (finished)
	Square Edge (unfinished)	Square Edge (unfinished)
Milling:	T&G, Double End Grooved	T&G, Double End Grooved

Herringbone ONLY available for AMITY, KIP, MATE, PROPER, BASTILLE, ACE, DOSH, and POSH 2.0.

Chevron options available upon request - contact reSAWN for more details.

SUSTAINABLE ATTRIBUTES:

Available as FSC[©]-Certified **CERTIFICATION:**



POSSIBLE LEED CREDITS: MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish)

MR 7 - Certified wood (as FSC®-Certified) EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Engineered) EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish) EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products (Engineered)

vers. 3/24