

PRODUCT SPECIFIC DATA:



CHALK
SOLID - SKU #BS-750601
ENGINEERED - SKU #BS-625601



DUSK
SOLID - SKU #BS-750602
ENGINEERED - SKU #BS-625602



TAPA
SOLID - SKU #BS-750604
ENGINEERED - SKU #BS-625604



UMBER
SOLID - SKU #BS-750606
ENGINEERED - SKU #BS-625606

CHALK, TAPA, UMBER, DUSK

SPECIES:	White Oak
CUT:	Original Cut
GRADE:	Character Grade
TREATMENT:	Textured Surface
FINISH:	Hardwax Oil
Janka Hardness (ASTM D 1037):	1,360
Flame Spread Class Rating (ASTM E 84):	Class III (C)
Flame Spread Index (ASTM E 84):	100
Smoke Developed Index (ASTM E 84):	100



SNOW
SOLID - SKU #BS-750605
ENGINEERED - SKU #BS-625605

SNOW	White Oak
SPECIES:	White Oak
CUT:	Original Cut
GRADE:	Character Grade
TREATMENT:	Textured Surface
FINISH:	Matte Polyurethane
Janka Hardness (ASTM D 1037):	1,360
Flame Spread Class Rating (ASTM E 84):	Class III (C)
Flame Spread Index (ASTM E 84):	100
Smoke Developed Index (ASTM E 84):	100

STANDARD MILLWORK:

Tongue & Groove, Endmatched

STANDARD DIMENSIONS & EDGE DETAIL:

	Solid	Engineered
Thickness:	3/4"	5/8" (4 mm wear layer)
Width:	5"	5"
Random Lengths:	2'-10'	2'-10'
Edges:	Microbevel	Microbevel

Note: Additional widths and lengths available upon request.

FINISH SPECS: Hardwax Oil

FLASH POINT	ASTM D 93: > 215°F (PenskyMartens)
RESISTANCE TO WATER	(NEN-EN 13442): no visual or tangible changes.
RESISTANCE TO WEAR	(NEN 2072 – Taber Abraser en CS 17 sanding wheels): strong absorption basantol liquid, only after 800 to 1000 rotations.
RESISTANCE TO HEAT	Until 212 °F

INSTALLATION GUIDE:

	Solid	Engineered
Above-grade	YES	YES
On-grade	YES	YES
Below-grade	NO	YES
Over Radiant Heat	YES	YES

ACCEPTABLE SUB-FLOORS and INSTALLATION METHODS - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor : Glue-down, Nail-down, Staple-down
 Concrete Sub-floor: Glue-down

SUSTAINABLE ATTRIBUTES:

CERTIFICATION	Available as FSC-Certified
POSSIBLE LEED CREDITS	MR 5 - Regional Materials MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish) MR 7 - Certified wood EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Hardwax-Oil Finish) EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish) EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products (Engineered)

Photo Disclaimer: Project and product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

Data from Forest Products Laboratory (FPL) General Technical Report (GTR) 190 - expected to be close to actual measurements of reSAWN TIMBER co.'s products.