

Project: Gensler Office
Location: Philadelphia, PA

Product: **KINOKO** from the **CHARRED** Collection

Gensler selected reSAWN's KINOKO shou-sugi-ban charred reclaimed hemlock wall cladding as the feature wall for their Philadelphia office.

Gensler is a global design firm that partners with clients to create more livable cities, smarter workplaces and more engaging leisure destinations. Their 4,500 professionals networked across 46 locations believe quality design can transform organizations and improve people's lives. Since 1965, they have helped clients achieve measurable business and organizational goals, delivering projects as large as a city and as small as a task light for an individual desk.

This project features reclaimed hemlock that has been burnt in the Japanese tradition of shou sugi ban. This ancient technique is gaining new life as a unique and modern interior and exterior wall cladding. The wood is carefully charred, doused in water, cooled, brushed to remove dust and loose debris, and then stained/sealed to create the unique designs you will find in the CHARRED collection.





Photo Disclaimer: Project and product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

Data from Forest Products Laboratory (FPL) General Technical Report (GTR) 190 - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

PRODUCT SPECIFIC DATA:



RECLAIMED HEMLOCK

GRADE: rustic

Janka Hardness: 420

Class Rating**: C (ASTM E 84)

Interior or Exterior Applications

KINOKO - reclaimed hemlock
SOLID - SKU #CH-750232

STANDARD MILLWORK: Tongue & Groove or S4S

STANDARD DIMENSIONS:

	Reclaimed Hemlock
Thickness:	+/- 7/8"
Width:	7"
Random Lengths:	4-10'

SOLID ONLY. Note: Additional widths and lengths available upon request.

FINISH SPECS: Burned, Brushed and finished with Translucent Sealer

FLASH POINT

115 °F (46 °C)

Burning wood gives it a charcoal barrier that is rot and fire resistant.