

Project: Jack Rogers
Location: Atlanta, GA
Architect: Green Light Architecture

Jack Rogers

Product: **ALABASTER** White Oak from the **RUSTIC MODERN** Collection

From Capri to Palm Beach and destinations around the globe, Jack Rogers is dedicated to the art of living well—and filling each day with simple pleasures and vibrant color. American in spirit, Jack Rogers was born out of resort style but has evolved into a lifestyle collection of year-round pieces. Jack Rogers' flagship store is located on Madison Avenue in NYC. They recently expanded to a new location in the exclusive Phipps Plaza in Atlanta. Green Light Architecture specified our ALABASTER White Oak for the flooring and project displays.



Photo credit: © Elana Munroe-Gregory 2013

PRODUCT SPECIFIC DATA:

reSAWN TIMBER co. worked with the Green Light Architecture to specify **ALABASTER** from the **RUSTIC MODERN** Collection. **ALABASTER** is available in solid or engineered construction in a variety of widths & lengths.

Flooring and Product Displays:

ALABASTER - White Oak - Character Grade - Engineered, Prefinished

5/8" thick (4 mm wear layer) X 5" wide X 2-10' RL

Tongue & Groove, Endmatched, Microbeveled Edges and Ends



ALABASTER

SPECIES:

GRADE:

FINISH:

Janka Hardness (ASTM D 1037):

Flame Spread Class Rating (ASTM E 84):

Flame Spread Index (ASTM E 84):

Smoke Developed Index (ASTM E 84):

White Oak

Character

Hardwax Oil

1,360

Class III (C)

100

100

STANDARD DIMENSIONS & EDGE DETAIL:

	Solid	Engineered
Thickness:	3/4"	5/8" (4 mm wear layer)
Width:	5"	5"
Random Lengths:	2'-10'	2'-10'
Edges:	Microbeveled *	Microbeveled *

Note: Additional widths and lengths available upon request.

* Microbeveled Edges recommended for prefinished products.

INSTALLATION GUIDE:

	Solid	Engineered
Above-grade	YES	YES
On-grade	YES	YES
Below-grade	NO	YES
Over Radiant Heat	YES	YES

SUSTAINABLE ATTRIBUTES:

CERTIFICATION Available as FSC-Certified

POSSIBLE LEED CREDITS

MR 5 - Regional Materials
 MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish)
 MR 7 - Certified wood (as FSC-Certified)
 EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Hardwax-Oil Finish)
 EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish)
 EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products (Engineered)

FINISH SPECS: Hardwax Oil

FLASH POINT ASTM D 93: > 215°F (PenskyMartens)

RESISTANCE TO WATER (NEN-EN 13442): no visual or tangible changes.

RESISTANCE TO WEAR (NEN 2072 – Taber Abraser en CS 17 sanding wheels): strong absorption basantol liquid, only after 800 to 1000 rotations.

RESISTANCE TO HEAT Until 212 °F

Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

Data from Forest Products Laboratory (FPL) General Technical Report (GTR) 190 - expected to be close to actual measurements of reSAWN TIMBER co.'s products.



Photo Disclaimer: Project and product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.