

Project: Madison Avenue Private Office  
Location: New York, NY  
Architect: CHANDLER PIERCE ARCHITECT

Product: MEDITATION - White Oak Flooring

Located in a boutique office building in the Plaza District on Madison Avenue in Midtown Manhattan, this private office features MEDITATION Rift & Quarter Sawn White Oak prefinished with Hardwax Oil from reSAWN TIMBER co.'s PRIMA Collection.



Photo credit: © reSAWN TIMBER co. 2013

Photo Disclaimer: Project and product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

## PRODUCT SPECIFIC DATA:

reSAWN TIMBER co. worked with CHANDLER PIERCE ARCHITECT to specify MEDITATION flooring for this private office in Manhattan. MEDITATION is available in solid and engineered construction, unfinished or prefinished and in a variety of widths and lengths. Any of the PRIMA Collection designs can also be customized to All Rift Sawn or All Quarter Sawn White Oak as desired.

### Flooring:

**MEDITATION** - Rift & Quarter Sawn White Oak - Engineered, Prefinished

5/8" thick (4 mm wear layer) X 5" wide X 2-10' random lengths

Tongue & Groove, Endmatched, Microbeveled Edges and Ends

Prefinished with Hardwax Oil



### MEDITATION

#### SPECIES:

GRADE:

CUT:

Janka Hardness (ASTM D 1037):

Flame Spread Class Rating (ASTM E 84):

Flame Spread Index (ASTM E 84):

Smoke Developed Index (ASTM E 84):

Shown finished with Hardwax Oil (Clear)

#### White Oak

Select/Better

Rift & Quarter Sawn

1,360

Class III (C)

100

100

## STANDARD DIMENSIONS, FINISH & EDGE DETAIL:

	Solid	Engineered
Thickness:	3/4"	5/8" (4 mm wear layer)
Width:	5"	5"
Random Lengths:	2'-10'	2'-10'
Edge Detail:	Microbeveled *	Microbeveled *
Finish:	Hardwax Oil (Clear)	Hardwax Oil (Clear)

Note: Additional widths and lengths available upon request.

\* Microbeveled Edges recommended for all prefinished products.

## INSTALLATION GUIDE:

	Solid	Engineered
Above-grade	YES	YES
On-grade	YES	YES
Below-grade	<b>NO</b>	YES
Over Radiant Heat	YES	YES

**ACCEPTABLE SUB-FLOORS and INSTALLATION METHODS** - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor : Glue-down, Nail-down, Staple-down

Concrete Sub-floor: Glue-down

## SUSTAINABLE ATTRIBUTES:

### CERTIFICATION

Available as FSC-Certified

MR 5 - Regional Materials

MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish)

MR 7 - Certified wood

### POSSIBLE LEED CREDITS

EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Hardwax-Oil Finish)

EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish)

EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products ( Engineered)

## FINISH SPECS: Hardwax Oil

### FLASH POINT

ASTM D 93: > 215°F (PenskyMartens)

### RESISTANCE TO WATER

(NEN-EN 13442): no visual or tangible changes.

### RESISTANCE TO WEAR

(NEN 2072 – Taber Abraser en CS 17 sanding wheels):  
strong absorption basantol liquid, only after 800 to 1000 rotations.

### RESISTANCE TO HEAT

Until 212 °F

Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

Data from Forest Products Laboratory (FPL) General Technical Report (GTR) 190 - expected to be close to actual measurements of reSAWN TIMBER co.'s products.