

Project: Private Residence - Massachusetts  
Location: Rochester, MA

Product: Rift & Quarter Sawn White Oak  
Character Grade  
FSC-Certified PURE

Located on a pond in Rochester, Massachusetts, this private residence features an open floor plan and warm, natural materials that compliment its wooded surroundings. Wood flooring by reSAWN TIMBER co. is a custom specification of FSC-Certified PURE Rift & Quarter Sawn White Oak in a Character Grade.




Photo Disclaimer: Project and product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

## PRODUCT SPECIFIC DATA:

Located on a pond in Rochester, Massachusetts, this private residence features an open floor plan and warm, natural materials that complement its wooded surroundings. Wood flooring by reSAWN TIMBER co. is a custom specification of FSC-Certified PURE Rift & Quarter Sawn White Oak in a Character Grade.

### Flooring:

Solid, Unfinished (site finished by others)  
 Rift & Quarter Sawn White Oak - Character Grade  
 3/4" thick X 5" wide X 1'-12' RL  
 Tongue & Groove, Endmatched, Square Edge (no microbevel)  
 FSC-Certified PURE



### SPECIES:

GRADE:	White Oak
CUT:	Character
Janka Hardness (ASTM D 1037):	Rift & Quarter Sawn
Flame Spread Class Rating (ASTM E 84):	1,360
Flame Spread Index (ASTM E 84):	Class III (C)
Smoke Developed Index (ASTM E 84):	100
Shown finished with Hardwax Oil (Clear)	100

## STANDARD DIMENSIONS, FINISH & EDGE DETAIL:

	Solid	Engineered
Thickness:	3/4"	5/8" (4 mm wear layer)
Width:	5"	5"
Random Lengths:	2'-10'	2'-10'
Edge Detail:	Microbeveled *	Microbeveled *
Finish:	Hardwax Oil (Clear)	Hardwax Oil (Clear)

Note: Additional widths and lengths available upon request.

\* Microbeveled Edges recommended for all prefinished products.

## INSTALLATION GUIDE:

	Solid	Engineered
Above-grade	YES	YES
On-grade	YES	YES
Below-grade	<b>NO</b>	YES
Over Radiant Heat	YES	YES

**ACCEPTABLE SUB-FLOORS and INSTALLATION METHODS** - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor : Glue-down, Nail-down, Staple-down

Concrete Sub-floor: Glue-down

## SUSTAINABLE ATTRIBUTES:

CERTIFICATION

Available as FSC-Certified

POSSIBLE LEED CREDITS

MR 5 - Regional Materials  
 MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish)  
 MR 7 - Certified wood  
 EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Hardwax-Oil Finish)  
 EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish)  
 EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products ( Engineered)