

Project: YOGASMOGA  
Location: Malibu, CA  
Design Firm: Axis Mundi Design

Product: **MEDITATION** rift & quarter sawn white oak - character grade

YOGASMOGA® is a yoga-inspired athletic apparel company that upholds the tenets of yoga through responsible and authentic business practices that inspire deep, direct and lasting connections with customers. Founded in 2013 by siblings Rishi and Tapasya Bali, the company is headquartered in New York City with significant production and retail operations in California and Massachusetts. YOGASMOGA crafts its products from innovative proprietary fabrics developed in its research and development facilities in California. As an expression of its ethos, YOGASMOGA uses only unretouched photography and manufactures its products domestically in the USA. YOGASMOGA created the NAMASKAR FOUNDATION to benefit health and education and facilitate micro-lending for residents of remote Himalayan villages.

YOGASMOGA recently opened a new store in the Malibu Country Mart. This shopping destination features unique and upscale boutiques, art galleries, restaurants, and personal services set in an astoundingly beautiful atmosphere. The store design incorporates reSAWN's MEDITATION rift & quarter sawn white oak prefinished with hardwax oil and customized in a character grade.

reSAWN and YOGASMOGA share many of the same values including a core of authenticity, a mantra of innovation, and products made responsibly in the USA to name but a few.

Axis Mundi Design was founded by John Beckmann in 2004. The New York-based design studio has a reputation for interdisciplinary work across the fields of architecture, interior and product design. The firm has conceived and executed residential, commercial and hospitality projects; a wide array of home and lifestyle products; as well as landscapes, art installations and sculpture. The firm's environmental sympathies are expressed in their conscientious selection of materials, and echoed in its appreciation for original architecture and its elements.







## MEDITATION - character grade

<b>SPECIES:</b>	<b>White Oak</b>
CUT:	Rift/Quarter Sawn
GRADE:	Character
FINISH:	Hardwax Oil
Janka Hardness (ASTM D 1037):	1,360
Flame Spread Class Rating (ASTM E 84):	Class III (C)
Flame Spread Index (ASTM E 84):	100
Smoke Developed Index (ASTM E 84):	100

### MEDITATION

SOLID - SKU #PR-750725

ENGINEERED - SKU #PR-625725

NWFA/NOFMA grading guidelines:

**QUARTER/RIFT SAWN:** Flooring that is marked or specified as QUARTER/RIFT SAWN or QUARTER/RIFT, is a combination of QUARTER SAWN and RIFT SAWN developing from the production run.

**QUARTER SAWN:** Flooring that is marked or specified as QUARTER SAWN or QUARTERED; at least 50% of the piece must contain Quartered characteristics. Quartered characteristics as defined by NOFMA are: In cross section the angle of the annual ring tangent to the face of the piece to be between 45° and 90°. Grain lines to be mostly parallel to the length of strips, and medullary ray flecks present and more than 1/16" wide.

**RIFT SAWN:** Flooring that is marked or specified as RIFT SAWN or RIFT; at least 75% of the piece must contain Rift characteristics. Rift characteristics as defined by NOFMA are: In cross section the angle of the annual ring tangent to the face of the piece to be between 30° to 60°. Grain lines to be mostly parallel to the length of strips and medullary ray flecks less than 1/16" wide.

MEDITATION is standardly select/better grade. A custom character grade was specified for Yogasmoga.

**SELECT GRADE:** A flooring product with coloration variations produced by differences of natural heartwood and sapwood, along with characters described. The face may contain: unlimited sound sapwood; slight imperfections in milling; a small tight knot every 3'; pin worm holes; burls and a reasonable amount of slightly open checks. Brown streaks should not extend the entire length of a piece. Two flag worm holes to every 8' are permitted. Slight imperfections in face work (torn grain) admitted. An intermittent, brown machine burn across the face not exceeding 1/4" width admitted.

**CHARACTER GRADE:** Contains prominent variations in coloration and varying characters. the following are not admitted: broken knots over 1" in diameter, large grub worm holes; and splits extending through the piece. open characters such as checks and knot holes are allowed and will be filled if floor is specified as prefinished. allowances include: sticker stain; varying wood characteristics, such as flag worm holes, heavy streaks, checks, and worm holes; and an occasional dark machine burn across the face not exceeding 1/2" wide.

Photo Disclaimer: Project and product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color; grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

Data from Forest Products Laboratory (FPL) General Technical Report (GTR) 190 - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

## STANDARD MILLWORK:

Tongue & Groove, Endmatched

## STANDARD DIMENSIONS & EDGE DETAIL:

	Solid	Engineered
Thickness:	3/4"	5/8" (4 mm wear layer)
Width:	5"	5"
Random Lengths:	2'-10'	2'-10'
Edges:	Microbevel	Microbevel

Note: Additional widths and lengths available upon request.

## FINISH SPECS: Hardwax Oil

FLASH POINT	ASTM D 93: > 215°F (PenskyMartens)
RESISTANCE TO WATER	(NEN-EN 13442): no visual or tangible changes.
RESISTANCE TO WEAR	(NEN 2072 – Taber Abraser en CS 17 sanding wheels): strong absorption basantol liquid, only after 800 to 1000 rotations.
RESISTANCE TO HEAT	Until 212 °F

## INSTALLATION GUIDE:

	Solid	Engineered
Above-grade	YES	YES
On-grade	YES	YES
Below-grade	<b>NO</b>	YES
Over Radiant Heat	YES	YES

**ACCEPTABLE SUB-FLOORS and INSTALLATION METHODS** - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor : Glue-down, Nail-down, Staple-down

Concrete Sub-floor: Glue-down

## SUSTAINABLE ATTRIBUTES:

CERTIFICATION	Available as FSC-Certified
POSSIBLE LEED CREDITS	MR 5 - Regional Materials MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish) MR 7 - Certified wood EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Hardwax-Oil Finish) EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish) EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products ( Engineered)