

NORTH AMERICAN BLACK WALNUT



WILLIAMSPORT
Finished with UV Oil
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

WESTPORT
Finished with Matte Polyurethane
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

LONGPORT
Finished with Matte Polyurethane
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

ROCKPORT
Finished with Matte Polyurethane
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide



FREEPORT
Finished with UV Oil
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

NEWBURYPORT
Finished with UV Oil
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

ADDITIONAL SPECIFICATIONS:

SPECIES:	North American Black Walnut
GRADE:	Character or Select
CUT:	Plain Sawn
APPLICATIONS:	Interior Flooring, Wall & Ceiling Cladding
LENGTHS:	2'-10' Random Lengths
MILLING:	T&G, Endmatched
EDGES:	Microbeveled Edges & Ends
Janka Hardness (ASTM D 1037):	1,010 *
Flame Spread Class Rating (ASTM E84):	Class II (B) **

GRADING GUIDELINES:

Character Grade

This grade includes live knots up to approximately 2-3/4" diameter and filled knots and star knots up to approximately 2" diameter. Knots are more prevalent. Sapwood may be present with only slight contrast to the heartwood. Width of sapwood streaks should be limited to approximately 1-5/8". Limited worm holes may be present as well as heart cracks and checking. Fill will be brown or black in tone.

Select Grade

This grade includes live knots up to approximately 1" diameter and filled knots up to approximately 5/8" diameter. Knots are limited in quantity. Sapwood may be present with only slight contrast to the heartwood. Width of sapwood streaks should be limited to approximately 3/4". Limited worm holes may be present. Fill will be brown or black in tone.

INSTALLATION GUIDE:

- Acclimatization is vital to minimize swelling & shrinking of material
- Visit resawntimberco.com's A+D Support page to download Installation Guidelines

Application	Engineered
Above-grade	YES
On-grade	YES
Below-grade	YES
Over Radiant Heat	YES

ACCEPTABLE SUB-FLOORS AND INSTALLATION METHODS - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor: Glue-down, Nail-down, Staple-down
Concrete Sub-floor: Glue-down

PACKAGING AND FREIGHT: All shipments are carefully packaged on 10'-12' long pallets

SUSTAINABLE ATTRIBUTES:

CERTIFICATION: Available as FSC®-Certified 

POSSIBLE LEED CREDITS: MR 5 - Regional Materials (based on project location)
MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish)
MR 7 - Certified wood (as FSC®-Certified)
EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Engineered)
EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish)
EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products (Engineered)

*Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

**Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2024. Testing is on unfinished and engineered - see attached for additional details. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

vers 11/24