

NORTH AMERICAN BLACK WALNUT



WILLIAMSPORT
Finished with hardwax oil
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

WESTPORT
Finished with matte polyurethane
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

LONGPORT
Finished with matte polyurethane
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

ROCKPORT
Finished with matte polyurethane
Character Grade:
ENG 3/4" (5mm) X 8" wide
Select Grade:
ENG 5/8" (4mm) X 7" wide

ADDITIONAL SPECIFICATIONS:

SPECIES:	North American Black Walnut
APPLICATIONS:	Flooring, wall cladding, and ceiling cladding
LENGTHS:	2'-10' Random Lengths
MILLING:	T&G, Endmatched
EDGES:	Microbeveled Edges and Ends
Janka Hardness (ASTM D 1037):	1,360 *
Flame Spread Class Rating (ASTM E84):	Class III (C) **

*Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

**Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2017. Testing is on unfinished and engineered - see attached for additional details. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

NORTH AMERICAN BLACK WALNUT



BRIDGEPORT is made with UNSTEAMED North American Black Walnut. Walnut that is unsteamed has the lighter sapwood present on the outer edges of a portion of the planks and maintains more dramatic color variations and characteristics.

BRIDGEPORT
UNSTEAMED
Finished with hardwax oil
Character Grade:
SOLID 3/4" X 5" wide
ENG 5/8" (4mm) X 5" wide

ADDITIONAL SPECIFICATIONS:

SPECIES:	North American Black Walnut
APPLICATIONS:	Flooring, wall cladding, and ceiling cladding
LENGTHS:	2'-10' random lengths
MILLING:	T&G, Endmatched
EDGES:	Microbeveled Edges and Ends
Janka Hardness (ASTM D 1037):	1,010 *
Flame Spread Class Rating (ASTM E84):	Class II (B) **
Flame Spread Index (ASTM E84):	75 **
Smoke Developed Index (ASTM E84):	125 **

*Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

**Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2017. Testing is on unfinished, solid wood - see attached for additional details. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

NORTH AMERICAN BLACK WALNUT



KURUMI
Finished with matte polyurethane
shou sugi ban charred
Character Grade:
ENG +/- 3/4" (5mm) X +/- 8" wide

ADDITIONAL SPECIFICATIONS:

SPECIES:	Black Walnut
APPLICATIONS:	Flooring, wall cladding, and ceiling cladding
LENGTHS:	2'-10' random lengths
MILLING:	T&G, Endmatched
EDGES:	Microbeveled Edges and Ends
Janka Hardness (ASTM D 1037):	1,010 *
Flame Spread Class Rating (ASTM E84):	Class II (B) **
Flame Spread Index (ASTM E84):	75 **
Smoke Developed Index (ASTM E84):	125 **

*Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN products.

**Flame Spread Class Rating, Flame Spread Index Data and Smoke Developed Index based on report from American Wood Council - 2017. Testing is on unfinished, solid wood - see attached for additional details. reSAWN's products are not tested but are expected to be close to actual measurements for comparable wood species -- can be treated to Fire Treated to Class A for Interior Applications - please call to inquire.

Photo Disclaimer: Product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

GRADING GUIDELINES:

Character Grade

Our character grade highlights the natural features in North American Black Walnut. We allow the presence of knots, cracks and sapwood. The allowance of up to 2” diameter knots, and open knots of up to 3/4” create a flooring grade that is both natural and sophisticated. Open voids are filled with a dark brown epoxy prior to finishing.

Select Grade

Our select grade North American Black Walnut is made using FAS (First and Seconds) lumber which is the highest possible grade. The grade is typically free from defects, but some are allowed. We allow for occasional pin knots and small filled knots up to 1/2” in diameter. Efforts are made to cull sap, but some edge or end sap may be present.

INSTALLATION GUIDE:

- Acclimatization is vital to minimize swelling & shrinking of material
- Visit resawntimberco.com’s A+D Support page to download Installation Guidelines

Application	Solid	Engineered
Above-grade	YES	YES
On-grade	YES	YES
Below-grade	NO	YES
Over Radiant Heat	YES	YES

ACCEPTABLE SUB-FLOORS AND INSTALLATION METHODS - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor: Glue-down, Nail-down, Staple-down
Concrete Sub-floor: Glue-down

PACKAGING AND FREIGHT: All shipments are carefully packaged on 12’ long pallets

SUSTAINABLE ATTRIBUTES:

CERTIFICATION: Available as FSC®-Certified 

POSSIBLE LEED CREDITS: MR 5 - Regional Materials (based on project location)
MR 6 - Rapidly Renewable Resource (Hardwax-Oil Finish)
MR 7 - Certified wood (as FSC®-Certified)
EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Engineered)
EQ 4.2 - Low-emitting materials: Paints & Coatings (Hardwax-Oil Finish)
EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products (Engineered)